


# M@XTEL® Comms Cable

## Aerial Self-Supported Telephone Cable (Figure 8)

### PEIUT IB

#### Cable Design

ACMA - AS/CA S008



- Drawing not to scale -

- **Multi-pair construction**
- **Conductor:** Annealed solid copper wire 0.64mm diameter (22 AWG) in compliance with AS/NZS 1125
- **Insulation:** Solid polyethylene compound in compliance with AS 1049
- **Cabling element:** Twisted pair
- **Colour code:** See table 1
- **Stranding of pairs:** Bunched (10 pair sub-units) / Units laid-up
- **Wrapping:** Polyethylene terephthalate tape
- **Drain wire:** Tinned annealed copper wire 0.5mm nominal diameter
- **Screen:** Aluminium / Polyethylene terephthalate tape
- **Bearer wire:** Galvanised steel wire in compliance with AS 1222.1
- **Sheath:** UV stabilised polyethylene in compliance with AS 1049

This self-supported copper telecommunications cable is designed for external aerial installation. GSW integral bearer is incorporated into the polyethylene sheath in 'figure 8' formation

#### Technical data

Number of Pairs		10	30	50	100
Cable nominal diameter	mm	10.4 x 16.5	16.7 x 24.8	21.0 x 29.4	29.2 x 39.9
Diameter over bearer (nominal)	mm	5	7		9
Cable nominal weight	kg/km	165	390	570	1080
GSW (IB) diameter	mm	1 / 2.50	7 / 1.25		7 / 1.60
Max. installation tension <sup>1</sup>	kN	2.0	3.5		5.8
Min. bending diameter	mm	20 x Cable OD			
Temperature range	°C	Installation -0 -> +50		Operation -10 -> +70	

Note 1: Over GSW (IB) messenger

#### Identification

##### Sheath Colour:

The standard outer sheath colour is black.

##### Sheath Marking:

The outer sheath is marked in 1 metre intervals as follows:

PRYSMIAN DW M@XTEL COMMS CABLE MM/YY XXX/0.64 PEIUT IB J/N ##### MADE IN AUSTRALIA \*\*\*\*\* >> | << \*\*\*\*\*

Where:

MM/YY = Month/Year of manufacture  
 XXX = Number of Pairs  
 ##### = Job Numbers  
 \*\*\*\*\* >> | << \*\*\*\*\* = Metre Marking with cut line

Electrical characteristics		
DC resistance (Max.)	Ω/km	56.4
Insulation resistance (Min.)	MΩ.km	40,000
Mutual capacitance (Max.)	nF/km	52
Capacitance unbalance, Pair to Pair (Max.)		
Corrected to 500m length	pF	150
Exponentially smoothed average, corrected to 1000m length	pF	37
Capacitance unbalance, Pair to Earth (Max.)		
Corrected to 1000m length – 10 Pair Cable	pF	800
– 30, 50 & 100 Pair Cables	pF	600

Note: All electrical characteristics are given at 20°C

**Table 1. Colour code / Pair and unit identification**

Pair number	Insulation colour		Pair number	Group colour	
	Wire a	Wire b			
1	White	Blue	1 to 10	Blue	Blue
2	White	Orange	11 to 20	Orange	Orange
3	White	Green	21 to 30	Green	Green
4	White	Brown	31 to 40	Brown	Brown
5	White	Grey	41 to 50	Grey	Grey
6	Red	Blue	51 to 60	White	Blue
7	Red	Orange	61 to 70	White	Orange
8	Red	Green	71 to 80	White	Green
9	Red	Brown	81 to 90	White	Brown
10	Red	Grey	91 to 100	White	Grey

Units : 10 pairs (pairs 1 to 10)

## Logistic

### Packing:

Timber drums generally to AS/NZS 2857 with flexible cable wrap protection

### Delivery Lengths:

Standard delivery length is 500 m with a tolerance of - 1% / + 3%

© PrysmianGroup 2020, All Rights Reserved

All sizes and values without tolerances are reference values. Specifications are for product as supplied by PrysmianGroup: any modification or alteration afterwards of product may give different result.

The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of PrysmianGroup. The information is believed to be correct at the time of issue. PrysmianGroup reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorised by PrysmianGroup.